

Electric Lift Table

- ▲ Heavy duty design.
- ▲ HW series lift tables meet EN norm and ANSI/ASME safety standards.
- ▲ These models can be used in above-floor or in-floor pit applications.
- Standard Safety Features
 - ▲ Upper platform lifted with aluminum safety bar preventing descent on contact with obstructions.
 - ▲ Low-tention (24V) control box with up-down buttons.
 - ▲ Internal power pack equipped with relief valve against overloading and compensated flow valve for controlled lowering speed.
 - ▲ Heavy dutty cylinders with drainage system and check valve tostop the lift table lowering in case of hose burst.
 - ▲ Safety clearance between scissors to prevent trapping during operation.
- Other Standard Features
 - ▲ Self lubricating bushings on pivot points.
 - ▲ Removable lifting eye to facilitable handling and lift table installation
 - ▲ High quality AC power packs are made in Europe



TECHNICAL DATA		MODEL							
		HW 1001	HW 1002	HW 1003	HW 1004	HW 1005	HW 1006	HW 1007	HW 1008
Capacity	kg	1000							
Platform Size	mm	820x1300	1000x1600	850x1700	1000x1700	850x2000	1000x2000	1700x1500	2000x1700
Base Frame Size	mm	640 x 1240		640 x 1580			1580 x 1320		
Lifting Height	mm	990				1300			
Lowering Height	mm	205				240			
Stroke	mm	785				1060			
Lift Time	second	30 - 40			45 - 50			35 - 45	
Power Pack		380 v 50 HZ, AC 1.1 kw							
Net Weight	kg	160	186	200	210	212	223	365	430

SPECIFICATION IS SUBJECT TO CHANGE WITHOUT NOTICE

Electric Lift Table

- ▲ Heavy duty design.
 - ▲ HW series lift tables meet EN norm and ANSI/ASME safety standards.
 - ▲ These models can be used in above-floor or in-floor pit applications.
- Standard Safety Features**
- ▲ Upper platform lifted with aluminum safety bar preventing descent on contact with obstructions.
 - ▲ Low-tention (24V) control box with up-down buttons.
 - ▲ Internal power pack equipped with relief valve against overloading and compensated flow valve for controlled lowering speed.
 - ▲ Heavy dutty cylinders with drainage system and check valve tostop the lift table lowering in case of hose burst.
 - ▲ Safety clearance between scissors to prevent trapping during operation.
- Other Standard Features**
- ▲ Self lubricating bushings on pivot points.
 - ▲ Removable lifting eye to facilitable handling and lift table installation
 - ▲ High quality AC power packs are made in Europe



TECHNICAL DATA		MODEL							
		HW 2001	HW 2002	HW 2003	HW 2004	HW 2005	HW 2006	HW 2007	HW 2008
Capacity	kg	2000							
Platform Size	mm	850x1300	1000x1600	850x1700	1000x1700	850x2000	1000x2000	1700x1500	2000x1800
Base Frame Size	mm	785 x 1220		785 x 1600				1600 x 1435	
Lifting Height	mm	1000		1300				1400	
Lowering Height	mm	230		250				250	
Stroke	mm	770		1050				1150	
Lift Time	second	20 - 25		25 - 35				25 - 35	
Power Pack		380v50HZ,AC2.2kw		380v50HZ,AC1.5kw				380v50HZ,AC2.2kw	
Net Weight	kg	235	268	289	300	300	315	415	500

SPECIFICATION IS SUBJECT TO CHANGE WITHOUT NOTICE

Electric Lift Table

- ▲ Heavy duty design.
 - ▲ HW series lift tables meet EN norm and ANSI/ASME safety standards.
 - ▲ These models can be used in above-floor or in-floor pit applications.
- Standard Safety Features**
- ▲ Upper platform lifted with aluminum safety bar preventing descent on contact with obstructions.
 - ▲ Low-tention (24V) control box with up-down buttons.
 - ▲ Internal power pack equipped with relief valve against overloading and compensated flow valve for controlled lowering speed.
 - ▲ Heavy dutty cylinders with drainage system and check valve tostop the lift table lowering in case of hose burst.
 - ▲ Safety clearance between scissors to prevent trapping during operation.
- Other Standard Features**
- ▲ Self lubricating bushings on pivot points.
 - ▲ Removable lifting eye to facilitable handling and lift table installation
 - ▲ High quality AC power packs are made in Europe



TECHNICAL DATA		MODEL							
		HW 4001	HW 4002	HW 4003	HW 4004	HW 4005	HW 4006	HW 4007	HW 4008
Capacity	kg	4000							
Platform Size	mm	1200x1700	1200x2000	1000x2000	1200x2000	1000x2200	1200x2200	1700x1500	2200x1800
Base Frame Size	mm	900x1600		900x2000				1620x1400	
Lifting Height	mm	1050		1400				1300	
Lowering Height	mm	240		300				350	
Stroke	mm	810		1100				950	
Lift Time	second	30 - 40		45 - 50				35 - 45	
Power Pack		380 v 50 HZ, AC 2.2 kw							
Net Weight	kg	375	405	470	490	480	505	570	655

SPECIFICATION IS SUBJECT TO CHANGE WITHOUT NOTICE