

Electric Pallet Truck WP 46 - 25



รายละเอียดผลิตภัณฑ์อาจมีการเปลี่ยนแปลงโดยมิได้แจ้งให้ทราบล่วงหน้า

Electric Pallet Truck 2.5 t

รายละเอียดผลิตภัณฑ์อาจมีการเปลี่ยนแปลงโดยมิได้แจ้งให้ทราบล่วงหน้า

Characteristics			
1.1	Manufacturer		PE
1.2	Model designation		WP46-25
1.3	Drive unit		Battery
1.4	Operator type		Rider
1.5	Load capacity	Q (kg)	2500
1.6	Load center	c (mm)	600
1.8	Load distance (Raised/ Lowered)	x (mm)	885/ 972
1.9	Wheelbase	y (mm)	1430
			905/ 992
			1450
Weights			
2.1	Service weight (Incl. battery)	kg	753
2.2	Axle loading, laden operator/load side	kg	962/ 1788
2.3	Axle loading, unladen operator/load side	kg	563/ 187
Wheels, Chassis			
3.1	Tyre type		PU/ PU
3.2	Tyre size, operator side		Φ248X75
3.3	Tyre size, load side		Φ80x120, Φ80X80
3.4	Balance wheels (dimensions)		Φ138x60.5
3.5	Wheels, number operator/load side (x=drive wheels)		1x+ 2/2 or 4
Dimensions			
4.4	Lift height	h_3 (mm)	120
4.9	Height of tiller arm in operating position, min/ max	h_{14} (mm)	1300(+180), 1200(+180)/940(+180)
4.15	Fork height, lowered	h_{13} (mm)	85
4.19	Overall length	l_1 (mm)	1770/1820(+70folded)(+440unfolded)
4.20	Length to face of forks	l_2 (mm)	620(+70folded)(+440unfolded)
4.21	Overall width	b_1/ b_2 (mm)	802
4.22	Fork dimensions	s/ e/ l (mm)	55/ 185/ 1150
4.25	Fork spread, min/ max	b_5 (mm)	540 / 685
4.32	Ground clearance, center of wheelbase	m_2 (mm)	35
4.33	Aisle width, 1000x1200 pallet crossways	Ast (mm)	1912 (folded)
4.34	Aisle width, 800x1200 pallet lengthways	Ast (mm)	2102 (folded)
4.35	Outer turning radius	Wa (mm)	1684 (folded)
			1705 (folded)
Performance			
5.1	Travel speed, laden/ unladen	km/ h	4/6
5.2	Lifting speed, laden/ unladen	m/ s	0.056/ 0.06
5.3	Lowering speed, laden/ unladen	m/ s	0.057/ 0.059
5.8	Maximum gradeability, laden/ unladen S_2 5 min.	%	5/ 7
5.10	Service brake		Electromagnetic
Drive			
6.1	Drive motor rating S_2 60 min.	kW	1.5
6.2	Lift motor rating at S_3 15%	kW	2
6.4	Battery voltage/ rated capacity (5h)	V/ Ah	24/ 210
6.5	Battery weight	kg	205
	Battery compartment dimensions l/ w/ h	mm	610x280x470
	Battery type		Industry battery
Others			
8.1	Type of drive control		AC
	Manufacturer		CURTIS
8.4	Sound level at operator's ear	dB (A)	70
8.6	Steering		Power steering

