

Four Scissor Lift Table

Heavy duty design.

High quality power unit from Europe.

Conforms to En1570 and ANSI/ASME safety standard.

Features:

- # Safety clearance between scissors to prevent from trapping.
 - # Installed aluminum safety bar to prevent from trapping while descending.
- Built-in relief valve and compensation flow control valve to fulfill overload protection and control lowering speed.
- There is safety valve to stop the table or keep slow descending in case of hose burst.
- Self-lubricating bushing in all pivot points to prolong the lifespan.



รายละเอียดผลิตภัณฑ์อาจมีการเปลี่ยนแปลงโดยมิได้แจ้งให้ทราบล่วงหน้า

TECHNICAL DATA		MODEL	
		HF 400	HF 800
Capacity	kg	400	800
Platform Width	mm	1000	1000
Platform Length	mm	1700	1700
Hydraulic Cylinder	set	2	2
Max. Height	mm	4140	4210
Min. Height	mm	600	700
Stroke	mm	3540	3510
Base size	mm	1600x1000	1606x1010
Raising time	second	30-40	65-75
Descending time	second	30-40	75-85
Power Pack		AC380V, 2.2KW	AC380V, 2.2KW
Net weight	kg	548	858

SPECIFICATION IS SUBJECT TO CHANGE WITHOUT NOTICE