Email: sales@liftkaz.com www.liftkaz.com

Electric Pallet Truck 30-460

Advantages:

Configuration And Perfornance

- Electronic power steering system, light and low noise.
- Drive unit floating bodies with patent design.
- AC Driving system, No carbon brush, maintenance free.
- USA CURTIS driving controller.
- Electronagnetic, regenerative braking system.
- Automatic lifting limit, extend the lift of the battery and motor.
- Side way battery, easy to replace.

Safety

- Curve automatic deceleration devices, more safe.
- Stepless speed control system, safe and quiet.
- Controller with multiple automatic protection.
- Emergency reversing deversing device / Emergency brake switch.



รายละเอียดผลิตภัณฑ์อาจมีการเปลี่ยนแปลงโดยมิได้แจ้งให้ทราบล่วงหน้า





Email: sales@liftkaz.com www.liftkaz.com

ELETRIC PALLET TRUCK		
Feature		
Manufacturer	PE	
Model	CBD30-460	
Load capacity	3000	kg.
Load center	600	kg.
Operating type	Stand On	
Dimension		
Min.fork lowered height	85	mm.
Max. fork lifting height	250	mm.
Overall fork width	550 / 685	mm.
Inside width between forkes	180 / 315	mm.
Fork length	1150 / 1220	mm.
Fork width	185	mm.
Fork thickness	55	mm.
Overall length	1916 / 2333	mm.
Overall width	790	mm.
Overall height(With handle)	1455	mm.
Overall height(Without handle)	845	mm.
Min.Turning radius	1746 / 2158	mm.
Min.Aisle width for pallets 800x1200	2046 / 2435	mm.
Min.Aisle width for pallets 1000x1200	2077 / 2458	mm.
Wheels		
Wheels type	PU	
Driving wheel size	Ø248x75	mm.
Front wheel size	Ø80x80 (Double wheels)	mm.
Balance wheel size	Ø155x55	mm.
Performance		
Travel speed,laden/unladen	5/5	km./h.
Lift speed,laden/unladen	20/25	mm./s.
Travel speed,laden/unladen	40/30	mm./s.
Gradeability,laden/unladen	5/7	%
Electrical configuration		
Drive motor	AC 1.5	kw
Lift motor	DC 1.2	kw
Steering motor	DC 0.5	kw
Battery voltage/capacity	24/270	V/Ah
Brake	Electromagnetic/Regenerative	
Controller	CURTIS	
Weight		
Battery weight	242	kg.
Service weight with battery	830	kg.
SPECIFICATION IS SUBJECT TO CHANGE WITHOUT NOTICE		