

Electric Reach Forklift ***EDQ 1000 EDQ 1200 EDQ 1500 EDQ 2000***



รายละเอียดผลิตภัณฑ์อาจมีการเปลี่ยนแปลงโดยมิแจ้งให้ทราบล่วงหน้า

Electric Reach Forklift

รายละเอียดผลิตภัณฑ์อาจมีการเปลี่ยนแปลงโดยมิแจ้งให้ทราบล่วงหน้า

TECHNICAL DATA		MODEL							
		EDQ 1030	EDQ 1045	EDQ 1230	EDQ 1245	EDQ 1530	EDQ 1545	EDQ 2030	EDQ 2045
Power		battery							
Operation		stand-on							
Load capacity	Q kg	1000		1200		1500		2000	
Lift height	A mm	3000	4500	3000	4500	3000	4500	3000	4500
Load centre	mm	500							
Fork carriage tilt (forward/backward) α/β (deg)		3 / 5							
Travel speed	km / h	7.7				8.8		8.5	
Lifting speed	mm / s	160		160		230		210	
Max gradeability (laden)	%	>12				>10			
Min turning radius	R mm	1430		1500		1580		1700	
Reach distance	B mm	550							
Service brake		mech							
Overall length	C mm	1820				2187			
Overall width	D mm	1020				1200			
Height of mast, lowered	H1 mm	2080	2185	2080	2185	2120	2205	2120	2205
Free lift height	mm	330							
Height of mast, extended	H2 mm	3945	5445	3945	5445	4000	5500	4000	5500
Height of overhead guard	E mm	2260							
Fork dimensions	mm	35 x 100 x 1070				45 x 120 x 1070			
Min ground clearance	mm	80							
Aisle width (pallet 1000 x 100)	Ast2 mm	2430	2430	2500	2430	2700	2700	2820	2700
Service weight	kg	1700	1850	1800	1950	2550	2750	2800	3000
Drive motor	kw	2.2				3.7			
Lift motor	kw	2				8.2			
Battery (5h)	V / Ah	24 / 390				48 / 450			
Tyres		polyurethane/solid tyre							
Size of front tyre	mm	250 x 120							
Size of rear tyre	mm	380 x 120							
Size of balancing tyre	mm	170 x 70							
Turning system		mech				hyd			
Speed control system		CURTIS / ZAPI							

SPECIFICATION IS SUBJECT TO CHANGE WITHOUT NOTICE