

TOW TRACTOR ETT Series

รถลากจูงไฟฟ้า Max. Load 3,000 / 4,000 / 6,000 Kg



รายละเอียดผลิตภัณฑ์อาจจะมีการเปลี่ยนแปลงโดยมิแจ้งให้ทราบล่วงหน้า

	Model	ETT-30	ETT-40	ETT-60	
Identification	Powersupply	Electric	Electric	Electric	
	Operating type	Sit on	Sit on	Sit on	
	Max traction weight	Q(kg)	3000	4000	6000
	Rated puling force (60min rating)	F(N)	1000	1000	1000
	Wheelbase (±5 mm)	γ(mm)	1231	1231	1231
Weights	Truck weight (with battery) (±10%)	kg	665	710	1020
	Axle loading,unloaded(front/rear) (±10%)	kg	330/516	330/516	330/516
Tire	Tyres	Rubber	Rubber	Rubber	
	Sees of front wheel	Φxw(mm)	3.50-5-6PR	3.50-5-6PR	3.50-5-6PR
	Sizes of rear wheel	Φxw(mm)	4.00-8-6PR	4.00-8-6PR	4.00-8-6PR
	Sizes of additional wheel	Φxw(mm)	-	-	-
	Wheels,number(x=drive wheel) front/rear		2/2x	2/2x	2/2x
	Tread,front	b10(mm)	245	245	245
	Tread, rear	b11 (mm)	744	744	744
Dimensions	Overall height	h6 (mm)	1245	1245	1245
		h14(mm)	-	-	-
	Hook height	h10(mm)	(240/326)/(290/376)/(340/426)		
	Overall length (± 5 mm)	l1 (mm)	1903	1903	1903
	Overall width (± 5 mm)	b1/b2 (mm)	860	860	860
	Ground clearance (Tread center) (Min)	m2 (mm)	104	104	104
	Turning radius (Min)	Wa (mm)	1590	1590	1590
Performanc		km/h	7/13	7/13	7/13
		N	1000	1000	1000
		N	4000	4000	4000
		%	7/15	7/15	7/15
	Brake type		Hydraulic	Hydraulic	Hydraulic
battery	Drive motor rating	kW	2.5	4	5
		V/Ah	24/135	48/100	48/135
	Banerywewght (±10%)	kg	169	169	169
Others	Type of drive control		AC MEGMEET	AC MEGMEET	AC MEGMEET
	Notve level at operatofs ear	dB(A)	<70	<70	<70
	Type of trailer coupling		Latch	Latch	Latch