

MINI TOW TRACTOR XT-50

รถลากจูงไฟฟ้า Max. Load 4,000 Kg



MINI TOW TRACTOR XT-50

รายละเอียดผลิตภัณฑ์อาจจะมีการเปลี่ยนแปลงโดยมิแจ้งให้ทราบล่วงหน้า

TECHNICAL DATA		Model
		XT50
Power supply		Battery
Operating Type		Sit-on
Max Traction weight	Kg	4000
Rated Pulling (60min Rating)	N(kgf)	1000
Wheels Base (± 5mm)	mm	955
Truck Weight (with battery) (± 10%)	Kg	783
Axle Loading unloaded (front/rear) (± 10%)	Kg	279/504
Tyres		Rubber
Sizes of front wheel	ø x 1mm	3.50-5-6PR
Sizes of rear wheel	ø x 1mm	4.00-8-6PR
Sizes of additional wheel	ø x 1mm	-
Wheel number(x=drive wheel) front/rear		1/2x
Tread, front	mm	0
Tread, rear	mm	724
Hook height	mm	305/355
Overall length (± 5mm)	mm	1728
Overall width (± 5mm)	mm	858
Ground Clearance (Treaded center) (Min.)	mm	85
Turning radius (Min.)	mm	1447
Drive speed unloaded/loaded	km/h	7/13
Platform Height	mm	371
Rated Pulling load/unload (60min Rating)	N(kgf)	1000
Max Pulling load/unload (5min Rating)	N(kgf)	4000
Max gardeability load/unload (5min Rating)	%	7/14
Brake type		Hydraulic
Battery voltage / nominal capacity	V/Ah	24/280
Battery Weight (± 10%)	Kg	285
Type of trailer coupling		Latch
Type of Drive Control		AC Curtis
Noise level at operator's ear	dB	<72
Specification is subject to change without notice		