

Full Electric Stacker WS 03 - 12



รายละเอียดผลิตภัณฑ์อาจมีการเปลี่ยนแปลงโดยมิได้แจ้งให้ทราบล่วงหน้า

Full Electric Stacker 1.2t รายละเอียดผลิตภัณฑ์อาจมีการเปลี่ยนแปลงโดยมิได้แจ้งให้ทราบล่วงหน้า

Characteristics		
1.1	Manufacturer	PE
1.2	Model designation	WS03-12
1.3	Drive unit	Battery
1.4	Operator type	Walkie (platform option)
1.5	Load capacity	Q (kg) 1200
1.6	Load center	c (mm) 600
1.9	Wheelbase	y (mm) 1270
Wheels, Chassis		
3.1	Tyre type	PU/PU
3.2	Tyre size, operator side (diameter x width)	mm $\Phi 248 \times 75$
3.3	Tyre size, load side (diameter x width)	mm $\Phi 84 \times 70$
3.4	Balance wheels (dimensions)	mm $\Phi 115 \times 55$
3.5	Wheels, number operator/load side (x=drive wheels)	1x+ 2/ 4
Dimensions		
4.2	Height, mast lowered	h_1 (mm) 1980/ 2135/ 2335
4.4	Lift height	h_3 (mm) 3000/ 3300/ 3600
4.5	Height, mast extended	h_4 (mm) 3500/ 3800/ 4100
4.9	Height of tiller arm in operating position, min/ max	h_{14} (mm) 1015/ 1450
4.10	Height of straddle arms or load wheel casing	h_8 (mm) 80
4.15	Fork height, lowered	h_{13} (mm) 85
4.19	Overall length	l_1 (mm) 1875
4.20	Length to face of forks	l_2 (mm) 843
4.21	Overall width	b_1/ b_2 (mm) 720
4.22	Fork dimensions	s/ e/ l (mm) 55/185/1150 or 1200
4.24	Fork carriage width	b_3 (mm) 700
4.25	Outside fork width, minimum/ maximum	b_5 (mm) 550/ 600/ 650
4.26	Width between straddle arms	b_4 (mm) 265/ 315/ 365
4.31	Ground clearance, laden, below mast	m_1 (mm) 30
4.32	Ground clearance, center of wheelbase	m_2 (mm) 30
4.33	Aisle width, 1000x1200 pallet crossways	As_t (mm) 2160
4.34	Aisle width, 800x1200 pallet lengthways	As_l (mm) 2130
4.35	Outer turning radius	Wa (mm) 1935/ 1525
Performance		
5.1	Travel speed, laden/ unladen	km/ h 3-5 / 3-5
5.2	Lifting speed, laden/ unladen	m/ s 0.13 / 0.23
5.3	Lowering speed, laden/ unladen	m/ s 0.13 / 0.23
5.8	Maximum gradeability, laden/ unladen S_2 5 min.	% 5/ 7
5.10	Service brake	Electromagnetic
Drive		
6.1	Drive motor rating S_2 60 min.	kW 1.5
6.2	Lift motor rating at S_3 15%	kW 3
6.4	Battery voltage/ rated capacity (5h)	V/ Ah 24 /210
6.5	Battery weight (with box)	kg 200
	Battery compartment dimensions l/ w/ h	mm 650/ 200/ 575
	Battery type	Industry
Others		
8.1	Type of drive control	AC
	Manufacturer	CURTIS
8.4	Sound level at operator's ear	dB (A) 70
8.6	Steering	Power steering

* Special lifting height available

